



Dumas

design Piero Lissoni

Armchair with backrest frame in double-paneled fir-wood and armrest and seat frame in multilayer poplar wood, padded in polyurethane foam covered with acrylic fiber layers.

Seat chassis, inset in the base frame, in solid fir-wood sprung with coated rubber elastic straps; padding in polyurethane foam covered in 100% polyether thermally bonded onto a polyamide velveteen backing.


Seat cushions in prewashed and sterilized goose down, stitched into separate compartments, with differentiated density polyurethane foam and Visco-soft insert, and covering in needle punched, resinated, non-woven polyester fiber, bonded onto a polyamide velveteen backing.

Backrest cushion in prewashed and sterilized goose down, stitched into separate compartments, with polyurethane foam insert. Fabric upholstery fully removable by zippers and Velcro fastenings. Fix leather upholstery for structure only.

Tubular steel feet Ø30mm for armchair and Ø22mm for easy chair, joined by a bracket, with bronzed epoxy powder coating and black PVC tips, or feet in solid wood footprint 50x50mm section for armchair and 40x40mm for easy chair, veneered Stone Oak®, screwed to a tubular steel bracket, painted with matt black epoxy powder.

Seat depth 61cm for armchair and 50cm for easy chair.

Armchair



Easy chair

